SKOBIFIXXs® 30

Prefab chimney shaft (Outer dimension: 150 x200 mm) for condensing technology, defined for buildings class 1–2 (Single family dwellings, fire-resistance class F30)

Order/enquiry form 2021

Description and brief explanation:

The overview diagram (Right) shows the assembled structure of the SKOBIFIXXs® 30 prefab shaft. The shaft comprises the following parts:

- 1 1M interlocking chimney shaft block, containing integral PPs flue D80 including bracing brackets
- Ceiling connection adapter with 100mm air-inlet inspection cap 80/125
- 3 Stack pack, comprising roof terminal, with options of pitched roof tile 25–45°, 5–25°, 35–55° or flat flashing
- 4 SKOBIFIX special adhesive in 3 kg tub
- 5 Support brackets

The interlocking shaft blocks 1 are 1 metre in length. The quantity of shaft parts required is determined by the length of the shaft starting at the ceiling above the heating appliance and extending to the roofing panel (around the shaft length up to the next whole number).

One ceiling connection adapter 2 and one stack pack 3 is required for each chimney shaft. Appropriate option should be selected or flat roof, or pitch of roof, height above roof and colour required.

A 3 kg tub of special adhesive 4 is sufficient to secure approx. 10 off interlocking chimney shaft block joints.

The support brackets **5** must be fixed in position in the area above the ceiling openings (except in the first ceiling above the heating appliance) and to the roof rafters at the uppermost position.

The number of support brackets required corresponds to the number of floors above the heating appliance.

Delivery conditions

The prices are given per unit exclusive of local valueadded tax and delivery costs. Non-exchanged EURO DIN palettes will be calculated at 13 EUR. We will deliver to an accessible unloading point. Unloading is not included. The customer must assume responsibility for unloading the goods.

3 Stack pack comprises Chimney cap x 1 Roof terminal x 1 Choice of angled pitched roof tile (or flat roof flashing) x 1 5 Finished/convertible attic Bracing Recess min 170x220 mm Defined for buildings class 1–2 5 Upper floor PPs flue D80. 4 All block interlocking joints to be secured with 'special adhesive Recess min Ø170 mm or rather 170 x 170 mm Ground floor Ground 2 level Inspection cap air-inlet Condensing boiler Basement

Latest revision: January 2021 (Subject to technical changes)



SKOBIFIXXs® 30 – Prefab chimney shaft (Outer dimension: 150×200 mm) for condensing technology, defined for buildings class 1–2 (Single family dwellings, fire-resistance class F30)

Order/enquiry form 2021	3 ·		ŕ			
Buyer (Name/Company)	Order	Order number				
	Comm	ission no.				
	Deliver	ry address				
Customer ID						
Delivery date						
Enquiry Order						
Article spec./description	Item-no.	Amount	EUR/unit			
1 Shaft blocks:				PPs pipe D80 Bracing bracket		
Shaft block 1,000 mm encorporating PPs flue D80, bracing bracket	730000			bracing bracket		
(40 x Shaft blocks/pallet, – standard Euro DIN	pallet) 730000			Shaft block		
Ceiling connection adapter, T piece and air-i	nlet 730003			Ceiling		
inspection cap; adapter dimensions 80/125, white powder coated (RAL 9010)				terminal Insulation shell		
				Wall plate		
				Connecting T-piece		
Connection expansion adapter D60/100–D80	730032			Inspection cap for air-inlet		
3 Stack packs:				Chimney cap		
Stack pack with roof terminal 0.4 m, pitched roof tile 25–45°, 600 x 700 mm, black	730006			PPs top flue pipe D80 (black) Roof terminal		
ditto in terracotta	730007			pipe Detachable		
Stack pack with roof terminal 1.0 m, pitched roof tile 25–45°, 600 x 700 mm, black	730008			connection Adjustable rain shield collar		
ditto in terracotta	730009					
Stack pack with roof terminal 0.4 m, flat flashing, black	730010			or B		
Stack pack with roof terminal 1.0 m, flat flashing, black	730012			Pitched roof tile Flat flashing 25–45°		
4 SKOBIFIX special adhesive 3 kg tub	710007					
5 Support bracket, (2-piece)	730004			0000		



Support bracket adjustable

Connecting support for cut bricks

SKOBIFIX builder's saw

730049

710069

730005

Sum

Total

Freight cost

SKOBIFIXXs® 30

Prefab chimney shaft (Outer dimension: 150 x 200 mm) for condensing technology, defined for buildings class 1–2 (Single family dwellings, fire-resistance class F30)

Order/enquiry form 2021

	icle spec./ description	Item-no.	Amount	EUR/unit			
	Stack pack with roof terminal 0.4 m, pitched roof tile 5–25°, 500 x 500 mm, black	730014			Roof terminal Skobifix Chimney cap		
	ditto in terracotta	730015			PPs top flue pipe D80, black Roof terminal pipe Detachable connection Adjustable rain shield collar Pitched roof tile Ø 125 5°-25°, 25°-45° or 35°-55° Flat roof collar Ø 125		
	Stack pack with roof terminal 1.0 m, pitched roof tile 5–25°, 500x500 mm, black	730016					
	ditto in terracotta	730017					
	Stack pack with roof terminal 0.4 m, pitched roof tile 35–55°, 500 x 500 mm, black	730018					
	ditto in terracotta	730019					
	Stack pack with roof terminal 1.0 m, pitched roof tile 35–55°, 500 x 500 mm, black	730020					
	ditto in terracotta	730021					
2	Roof terminal, painted silver, 0.4 m	730022					
	Roof terminal, painted silver, 1.0 m	730023					
3	Pitched roof tile, DN 125, 5–25°, black	710095					
	Pitched roof tile, DN 125, 25–45°, black	710099					
	Pitched roof tile, DN 125, 35–55°, black	710097					
4	Flat roof collar D125	000251			Ø 410		
5	Roof terminal extension, 500 mm, black	730083			Connecting		
	ditto in terracotta	730082					
	ditto in painted silver	709998					
	Roof terminal extension, 1000 mm, black	710085					
	ditto in terracotta	710084					
	ditto in painted silver	709999					
6	Tensioning clamp for roof terminal extension D135, black, with 15m rope and 3 rope tensioners	710158					
	ditto in terracotta	710159					
	ditto in galvanized	710160					
7	Ceiling connection adapter with connecting elbow, 87°, D80/125, powder-coated, white	730024			Ceiling terminal Insulation shell Wall panel Connection elbow 87°		
		Sum					
		Freight cost					
		Total					