UNIFIX »Chimney for condensing boilers«

System lightweight shaft $L_A90\ 240\ x\ 240\ mm$ / Ø 165 mm - comprising flue pipe D80 PPs

Order/enquiry form 2021

Description and brief explanation:

The overview diagram to the right shows the assembled structure of the *UNIFIX* lightweight shaft. The shaft comprises the following components:

- 1 Shaft element 500 mm containing integral PPs flue pipe D80 incl. spacer PP
- 2 Basic package comprising:
 - 1 pc. Ceiling connection element
 - 1 pc. Roof terminal terracotta or black
 - 1 pc. Pitched roof tile, adjustable 25–45° roof pitch (other inclinations on request)
 - or Flat roof collar
 - 1 pc. Anchor plate
- 3 Bag special adhesive (12 kg)
- 4 Support brackets with insulation insert

The shaft blocks 1 are 0.5 m in length and contain flue pipe and spacer. The quantity of shaft elements required is determined by the length of the shaft starting at the ceiling above the heating appliance and extending to the roofing panel

For the shaft construction you need a basic package Please observe the several variants for pitched roof, flat roof, different heights above roof and colours terracotta and black.

One package of special adhesive 3 is sufficient for approximately 20 connections between shaft elements.

The support brackets 4 must be fixed in position in the area above the ceiling openings (except in the first ceiling above the heating appliance) and to the roof rafters at the uppermost position. The number of support brackets required corresponds to the number of floors above the heating appliance.

Delivery conditions

The prices are given per unit exclusive of local value-added tax and delivery costs. Non-exchanged EURO DIN palettes will be calculated at 13 EUR. We will deliver to an accessible unloading point. Unloading is not included. The customer must assume responsibility for unloading the goods.

Use regardless of the building height. Chimney cap Roof terminal Choice of angled pitched roof tile or flat roof flashing Support bracket Anchor Support Finished/convertible attic Recess min 260x260 mm Support Upper floor PPs flue D80 UNIFIX shaft component All element joints to be secured Recess min Ø170 mm or rather 170 x 170 mm Ceiling connection adapter Ground floor Ground vlaau Inspection cap Basement Condensing boiler

Latest revision: January 2021 (Subject to technical changes)



UNIFIX »Chimney for condensing boilers« – System lightweight shaft L_A 90, 240 x 240 mm/ Ø 165 mm – comprising flue pipe D80 PPs

Order/enquiry form 2021

Buyer (Name/Company)	Order n	umbor				
Buyer (Name/Company)	Order n	number				
	Commission no.					
	Delivery	/ address				
Customer ID						
Enquiry Order Delivery date						
Article spec./description	Item-no.	Amount	EUR/unit			
1 Shaft elements:				PPs pipe D80		
Shaft element 240 x 240 x 500 mm comprising PPs flue gas pipe D80, spacer	750001			Spacer		
Shaft element 240 x 240 x 1000 mm (2x 500)	750000					
comprising PPs-flue gas pipe D80, spacer				Shaft element		
2 Basic package comprising:				Ceiling Connection element		
1 pc. Ceiling connection element incl. inspection				Ceiling		
T-piece, dim. D80/125 1 pc. Roof terminal (colour and heights see below)				Insulation shell Wall plate		
1 pc. Pitched roof tile, adjustable or Flat roof collar				vvaii piate		
1 pc. Anchor plate						
				Connecting T-piece Inspection cap		
Stack packs:				for air-inlet Roof terminal		
Stack pack with roof terminal 0.4 m,	750003			Chimney cap		
pitched roof tile 25–45°, black	750004			PPs top flue pipe		
Stack pack with roof terminal 1.0 m,	750004			D80 (black) Roof terminal pipe		
pitched roof tile 25–45°, black	750005			Koor terminar pipe		
ditto in terracotta	750006					
Stack pack with roof terminal 0.4 m,	750007			Anchor plate		
flat roof flashing, black Stack pack with roof terminal 1.0 m,	750008					
flat flashing, black	750008			or S		
- 						
				Pitched roof tile Flat roof 25°–45° collar		
Bag special adhesive (12 kg)	700091					
4 Support bracket, (2-piece)	750009			0 0		



5 Expansion adapter D60/100–80/125 (eccentr.)

730032

Order/enquiry form 2021

ticle spec./description	Item-no.	Amount	EUR/unit	
Stack pack with roof terminal 0.4 m, pitched roof tile 5–25°, 500 x 500 mm, black	750023			Roof terminal Chimney cap
ditto in terracotta	750024			PPs top flue pipe D60, black Roof terminal pipe Detachable connection
Stack pack with roof terminal 1.0 m, pitched roof tile 5–25°, 500 x 500 mm, black	750025			
ditto in terracotta	750026			
Stack pack with roof terminal 0.4 m, pitched roof tile 35–55°, 500 x 500 mm, black	750031			
ditto in terracotta	750032			Ø 125 5°–25°,
Stack pack with roof terminal 1.0 m, pitched roof tile 35–55°, 500 x 500 mm, black	750033			500 or 35°-55
ditto in terracotta	750034			500
				Ceiling connection adapter Ceiling terminal Insulation shell Wall panel Connection T-piece Inspection cap for air-inlet
Roof terminal extension, 500 mm, black	710083			
ditto in terracotta	710082			
Roof terminal extension, 1000 mm, black	710085			
ditto in terracotta	710084			Connecting
Tensioning clamp for roof terminal extension D135, black, with 15m rope and 3 rope tensioners	710158			
ditto in terracotta	710159			
ditto in galvanized	710160			
Builder's saw	710069			C. 2
	Sum			
	Freight cost			
	Total			İ